


Electric Pump for Oil Model PEO - 10 N

Specifications

Number of pumping elements	From 1 to 3
Discharge/cycle with fixed pumping elements	0,16 cm ³
Discharge/cycle with adjustable pumping elements	0,01 - 0,16 cm ³
Three-phase motor	Please refer to Table 1
Electrical minimum level	1,5 A 250 V AC - 200 V DC 50 W
Capacity of reservoir	10 liters
Working pressure	500 kg/cm ² (7260 psi) maximum
Lubricant	Oil 50-1500 cSt
Temperature	From -20 °C to +80 °C
Outlet fitting	1/4" BSP

Table 1 - Three-phase motor

Working voltage	220-240/380-420/254-280/440-480 V
Cycles	50/60 Hz
Current	0,6 - 0,35 A
Power	90 W
Protection	IP - 55
Service	Continuous S1
Insulation	Class F
Constructive layout	B14
Type	MEC - 56



Purchasing codes

Code	Reference	Type	Fixed flow	Variable flow	Reduction	Frequency	
						50 Hz	60 Hz
11094	00.924.0	PEO-10/30	***		1:30	46	55
11095	00.924.3	PEO-10/30R		***	1:30	46	55

Standard version with single outlet. Other pumping elements may be ordered separately.