


Electrical Pump for Grease Model PEG-2

Specifications

Number of pumping elements	From 1 to 3
Discharge/cycle with fixed pumping elements	0,16 cm ³
Discharge/cycle with adjustable pumping elements	0,01 - 0,16 cm ³
Number of cycles per minute	15
Motor	24 V DC - 30 W - 1,5 A 12 V DC - 40 W - 3 A
Minimum level electrical switch	2 A- 230 V AC/DC - 40 W - IP54
Capacity of reservoir	2 kg
Working pressure	250 kg/cm ² (3630 psi) maximum
Lubricant	Soft grease maximum NLGI - 2
Temperature	From -20 °C to +80 °C
Outlet fitting	1/4" BSP



Purchasing codes

Code	Reference	Type	Electric Level	Fixed Flow	Adjustable Flow	Voltage
5137	90.882.1	PEG - 2		***		12 V DC
5138	90.915.1	PEG - 2 LV	***	***		12 V DC
5139	90.902.1	PEG - 2 R			***	12 V DC
5140	90.921.1	PEG - 2 R LV	***		***	12 V DC
5136	90.882.0	PEG - 2		***		24 V DC
5134	90.915.0	PEG - 2 LV	***	***		24 V DC
5141	90.902.0	PEG - 2 R			***	24 V DC
5135	90.921.0	PEG - 2 R LV	***		***	24 V DC

Standard version is supplied with single outlet. Other pumping elements may be ordered separately.