

Electrical Pump for Grease Model PEG - 2N

Specifications


Number of pumping elements	From 1 to 3
Flow / cycle with fixed pumping elements	0.16 cm ³
Flow / cycle with adjustable pumping elements	0.01 - 0.16 cm ³
Number of turns per minute	15
Motor	24 V DC - 30 W - 1,5 A 12 V DC - 40 W - 3 A
Minimum electrical level	2 A - 230 V AC/DC - 40 W-IP54
Reservoir capacity	2 kg
Maximum operating pressure	250 kg/cm ² (3,630 psi)
Lubricant	Grease max NGLI - 2
Temperature	From -20 °C to +80 °C
Outlet union	1/4" BSP

Notes

- Standard version is equipped with a single outlet.
- Other pumping elements may be ordered in separate.

Optionals

- Minimum level electrical switch
- Timer



Purchasing codes

Code	Reference	Type	Electric Level	Flow		Timer	Voltage
				Fixed	Adjustable		
5275	90.915.0	PEG - 2 N	***	***			24 VDC
5274	90.915.0T	PEG - 2 N	***	***		***	24 VDC
11357	90.882.0T	PEG - 2N		***		***	24 VDC
5135	90.921.0	PEG - 2N	***		***		24 VDC
11438	90.921.0T	PEG - 2N	***		***	***	24 VDC
11439	90.902.0T	PEG - 2N			***	***	24 VDC